



中国认可  
国际互认  
检测  
TESTING  
CNAS L6478



# TEST REPORT

Reference No..... : WTF19F12091531E  
 Applicant..... : Mid Ocean Brands B. V.  
 Address..... : 7/F., Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon,  
 Hong Kong  
 Manufacturer ..... : 108694  
 Product Name..... : Twist ball pen with light  
 Model No..... : MO9142  
 Standards..... : EN 55015:2013+A1:2015  
 EN 61547:2009  
 Date of Receipt sample .... : 2019-12-30  
 Date of Test ..... : 2019-12-30 to 2020-01-06  
 Date of Issue..... : 2020-01-07  
 Test Report Form No. .... : WEL-55015A-01A  
 Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Foshan) Co., Ltd.**

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,  
 Chencun, Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398 Fax:+86-757-23811381 E-mail:info@waltek.com.cn

Compiled by:

Roy Hong / Project Engineer

Approved by:



Chen Yang / Manager

## 1 Test Summary

EMISSION				
Test Item	Test Standard	Class / Severity	Result	
Radiated Electromagnetic Disturbance, 9kHz to 30MHz	EN 55015:2013+A1:2015	Clause 4.4.1	Pass	
Radiated Emission, 30MHz to 300MHz	EN 55015:2013+A1:2015	Clause 4.4.2	Pass	
IMMUNITY (EN 61547: 2009)				
Test Item	Test Method	Class / Severity	Performance Criteria	Result
Electrostatic Discharge(ESD)	IEC 61000-4-2:2008	±4 kV Contact ±8 kV Air	B	Pass
Radio-Frequency Electromagnetic Fields (80MHz to 1GHz)	IEC 61000-4-3:2010	3V/m, 80%, 1kHz, Amp. Mod.	A	Pass

Remark:

Pass	Test item meets the requirement
Fail	Test item does not meet the requirement
N/A	Test case does not apply to the test object

<b>2 Contents</b>	Page
<b>COVER PAGE</b> .....	<b>1</b>
<b>1 TEST SUMMARY</b> .....	<b>2</b>
<b>2 CONTENTS</b> .....	<b>3</b>
<b>3 GENERAL INFORMATION</b> .....	<b>4</b>
3.1 GENERAL DESCRIPTION OF E.U.T. ....	4
3.2 DETAILS OF E.U.T. ....	4
3.3 DESCRIPTION OF SUPPORT UNITS .....	4
3.4 STANDARDS APPLICABLE FOR TESTING .....	4
3.5 TEST FACILITY .....	5
3.6 SUBCONTRACTED .....	5
3.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
<b>4 EQUIPMENT USED DURING TEST</b> .....	<b>6</b>
4.1 MEASUREMENT UNCERTAINTY .....	6
<b>5 EMISSION TEST RESULTS</b> .....	<b>7</b>
5.1 RADIATED ELECTROMAGNETIC DISTURBANCE, 9KHZ TO 30MHZ .....	7
5.1.1 <i>E.U.T. Operation</i> .....	7
5.1.2 <i>Block Diagram of Test Setup</i> .....	8
5.1.3 <i>Measurement Data</i> .....	8
5.1.4 <i>Radiated Electromagnetic Disturbance Test Data, 9kHz to 30MHz</i> .....	9
5.2 RADIATED EMISSION, 30MHZ TO 300MHZ .....	12
5.2.1 <i>E.U.T. Operation</i> .....	12
5.2.2 <i>Block Diagram of Setup</i> .....	12
5.2.3 <i>Measurement Data</i> .....	13
5.2.4 <i>Radiated Emission Test Data</i> .....	13
<b>6 IMMUNITY TEST RESULTS</b> .....	<b>15</b>
6.1 PERFORMANCE CRITERIA .....	15
6.2 ELECTROSTATIC DISCHARGE (ESD) .....	16
6.2.1 <i>E.U.T. Operation</i> .....	16
6.2.2 <i>Block Diagram of Setup</i> .....	17
6.2.3 <i>Direct Discharge Test Results</i> .....	18
6.2.4 <i>Indirect Discharge Test Results</i> .....	18
6.3 RADIO-FREQUENCY ELECTROMAGNETIC FIELDS, 80MHZ TO 1GHZ .....	19
6.3.1 <i>E.U.T. Operation</i> .....	19
6.3.2 <i>Block Diagram of Setup</i> .....	20
6.3.3 <i>Test Results</i> .....	20
<b>7 PHOTOGRAPHS – TEST SETUP</b> .....	<b>21</b>
7.1 PHOTOGRAPH – RADIATED ELECTROMAGNETIC DISTURBANCE TEST SETUP .....	21
7.2 PHOTOGRAPH – RADIATED EMISSION TEST SETUP, 30MHZ TO 300MHZ .....	21
7.3 PHOTOGRAPH – ESD IMMUNITY TEST SETUP .....	22
7.4 PHOTOGRAPH – RADIO-FREQUENCY ELECTROMAGNETIC FIELDS IMMUNITY TEST SETUP .....	22
<b>8 PHOTOGRAPHS – CONSTRUCTIONAL DETAILS</b> .....	<b>23</b>
8.1 EUT – EXTERNAL VIEW .....	23
8.2 EUT – INTERNAL VIEW .....	24

### 3 General Information

#### 3.1 General Description of E.U.T.

Product Name ..... : Twist ball pen with light  
Model No. .... : MO9142  
Remark..... : ---

#### 3.2 Details of E.U.T.

Technical Data..... : Battery 4.5V

#### 3.3 Description of Support Units

The EUT has been tested as an independent unit. MO9142 is the test sample. All tests were performed in the condition of Battery 4.5V.

#### 3.4 Standards Applicable for Testing

The tests were performed according to following standards:

EN 55015:2013+A1:2015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547:2009	Equipment for general lighting purposes — EMC immunity requirements



### 3.5 Test Facility

The test facility has a test site registered with the following organizations:

- **ISED – Registration No.: 21895**

Waltek Services (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Innovation, Science and Economic Development Canada (ISED). The acceptance letter from the ISED is maintained in our files. Registration ISED number: 21895, March 12, 2019

- **FCC – Registration No.: 820106**

Waltek Services (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106, August 16, 2018

- **NVLAP – Lab Code: 600191-0**

Waltek Services (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

### 3.6 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes       No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

### 3.7 Abnormalities from Standard Conditions

None.

#### 4 Equipment Used during Test

Radiated Electromagnetic Disturbance (9kHz to 30MHz)					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESCI	101178	Valid
2	Three Loops Antenna	SCHWARZBECK	HXYZ9170	213	Valid
Radiated Emission					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	EMI Test Receiver	R&S	ESR7	101566	Valid
2.	Active Loop Antenna	SCHWARZBECK	FMZB1519B	00004	Valid
3.	Trilog Broadband Antenna	SCHWARZBECK	VULB 9162	9162-117	Valid
ESD					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	ESD Simulator	TESEQ	NSG437	521	Valid
Radio-Frequency Electromagnetic Fields					
Item	Equipment	Manufacturer	Model No.	Serial No.	Calibration Status
1.	RF Power Amplifier	OPHIR	5225R	1051/1712	Valid
2.	RF Power Amplifier	OPHIR	5293RE	1051/171	Valid
3.	Stacked double logarithmic periodic antenna	SCHWARZBECK	STLP9128E-SPECIAL	STLP 9128E	Valid
4.	Stacked double logarithmic periodic antenna	SCHWARZBECK	STLP 9149	STLP 9149 #476	Valid
5.	RF signal generator	Agilent	N5181A	MY48080720	Valid
6.	Power meter	RS	NRP6A	101133	Valid
7.	Power meter	RS	NRP6A	101134	Valid
8.	Electric field probe	Narda S.T.S/PMM	EP 601	---	Valid

#### 4.1 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiated Electromagnetic Disturbance	9kHz to 30MHz	±3.00dB	(1)
Radiated Emission	30MHz~300MHz	±4.56dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 5 Emission Test Results

### 5.1 Radiated Electromagnetic Disturbance, 9kHz to 30MHz

<b>Test Requirement</b> .....	:	EN 55015 Clause 4.4.1
<b>Test Method</b> .....	:	EN 55015 Clause 9.1
<b>Test Result</b> .....	:	Pass
<b>Frequency Range</b> .....	:	9kHz to 30MHz
<b>Class/Severity</b> .....	:	Table 3a of EN55015

#### 5.1.1 E.U.T. Operation

##### Operating Environment:


<b>Temperature</b> .....	:	23.1°C
<b>Humidity</b> .....	:	43.2%RH
<b>Barometric Pressure</b> .....	:	101.2kPa

##### EUT Operation:

<b>Input Voltage</b> .....	:	Battery 4.5V
<b>Operating Mode</b> .....	:	Lighting mode

### 5.1.2 Block Diagram of Test Setup

The Radiated Electromagnetic Disturbance (9kHz to 30MHz) test was performed in accordance with the EN 55015.



### 5.1.3 Measurement Data


According to the data in section 5.2.4, the EUT complied with the EN 55015 standards.





**5.1.4 Radiated Electromagnetic Disturbance Test Data, 9kHz to 30MHz**


Loop X:



No.	Freq. (MHz)	Reading (dBuA)	Factor (())	Result (dBuA)	Limit (dBuA)	Margin (dB)	Detector	Remark
	0.009				90			
	10				58			
	30.0				20			




Loop Y:



No.	Freq. (MHz)	Reading (dBuA)	Factor (())	Result (dBuA)	Limit (dBuA)	Margin (dB)	Detector	Remark
-----	-------------	----------------	-------------	---------------	--------------	-------------	----------	--------



**Loop Z:**



No.	Freq. (MHz)	Reading (dBuA)	Factor (())	Result (dBuA)	Limit (dBuA)	Margin (dB)	Detector	Remark

## 5.2 Radiated Emission, 30MHz to 300MHz

**Test Requirement**..... : EN 55015 Clause 4.4.2  
**Test Method**..... : Clause 10 of CISPR 22  
**Test Result**..... : Pass  
**Frequency Range**..... : 30MHz to 300MHz  
**Class/Severity**..... : Table 3b of EN55015

### 5.2.1 E.U.T. Operation

#### Operating Environment:


**Temperature** ..... : 23.1°C  
**Humidity**..... : 43.2%RH  
**Atmospheric Pressure**..... : 101.2kPa

#### EUT Operation :

**Input Voltage** ..... : Battery 4.5V  
**Operating Mode**..... : Lighting mode

### 5.2.2 Block Diagram of Setup

The Radiated Emission test was performed in the 3m Semi- Anechoic Chamber test site and accordance with CISPR16-2-3.





### 5.2.3 Measurement Data

The maximised peak emissions from the EUT was scanned and measured for Horizontal & Vertical polarisation. Quasi-peak measurements were performed if peak emissions were within 6dB of the limit line.

### 5.2.4 Radiated Emission Test Data


#### Vertical Polarization:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	32.5928	7.09	12.24	19.33	40.00	-20.67	QP	
2	44.8871	6.71	14.39	21.10	40.00	-18.90	QP	
3	77.2896	10.24	9.64	19.88	40.00	-20.12	QP	
4	94.6501	6.89	11.00	17.89	40.00	-22.11	QP	
5	168.7024	8.81	11.47	20.28	40.00	-19.72	QP	
6	199.5819	10.77	13.07	23.84	40.00	-16.16	QP	



**Horizontal Polarization :**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	43.5633	6.58	15.18	21.76	40.00	-18.24	QP	
2	76.9345	16.06	9.51	25.57	40.00	-14.43	QP	
3	82.6269	12.52	9.45	21.97	40.00	-18.03	QP	
4	95.3062	6.13	10.44	16.57	40.00	-23.43	QP	
5	152.4478	7.54	10.48	18.02	40.00	-21.98	QP	
6	203.2925	6.50	13.07	19.57	40.00	-20.43	QP	



## 6 Immunity Test Results

### 6.1 Performance Criteria

**Performance criterion A:** During the test, no change of the luminous intensity shall be observed and the regulating control, if any, shall operate during the test as intended.

**Performance criterion B:** During the test, the luminous intensity may change to any value. After the test, the luminous intensity shall be restored to its initial value within 1 min. Regulating controls need not function during the test, but after the test, the mode of the control shall be the same as before the test provided that during the test no mode changing commands were given.

**Performance criterion C:** During and after the test, any change of the luminous intensity is allowed and the lamp(s) may be extinguished. After the test, within 30 min, all functions shall return to normal, if necessary by temporary interruption of the mains supply and/or operating the regulating control.

## 6.2 Electrostatic Discharge (ESD)

<b>Test Requirement</b> .....	:	EN 61547
<b>Test Method</b> .....	:	IEC 61000-4-2
<b>Test Result</b> .....	:	Pass
<b>Discharge Impedance</b> .....	:	330Ω / 150pF
<b>Discharge Voltage</b> .....	:	Air Discharge: ±8kV Contact Discharge: ±4kV HCP & VCP: ±4kV
<b>Polarity</b> .....	:	Positive & Negative
<b>Number of Discharge</b> .....	:	Minimum 10 times at each test point
<b>Discharge Mode</b> .....	:	Single Discharge
<b>Discharge Period</b> .....	:	1 second minimum

### 6.2.1 E.U.T. Operation

#### Operating Environment:

<b>Temperature</b> .....	:	22.3°C
<b>Humidity</b> .....	:	47.1%RH
<b>Barometric Pressure</b> .....	:	101.1kPa


#### EUT Operation:

<b>Input Voltage</b> .....	:	Battery 4.5V
<b>Operating Mode</b> .....	:	On mode



## 6.2.2 Block Diagram of Setup

The ESD test was performed in accordance with the IEC 61000-4-2.





### 6.3 Radio-Frequency Electromagnetic Fields, 80MHz to 1GHz

<b>Test Requirement</b> .....	:	EN 61547
<b>Test Method</b> .....	:	IEC 61000-4-3
<b>Test Result</b> .....	:	Pass
<b>Frequency Range</b> .....	:	80MHz to 1GHz
<b>Test level</b> .....	:	3V/m
<b>Modulation</b> .....	:	80%, 1kHz Amplitude Modulation.
<b>Face of EUT</b> .....	:	Front, Back, Left, Right
<b>Antenna polarisation</b> .....	:	Horizontal & Vertical

#### 6.3.1 E.U.T. Operation

##### Operating Environment:


<b>Temperature</b> .....	:	23.7°C
<b>Humidity</b> .....	:	47.2%RH
<b>Barometric Pressure</b> .....	:	100.2kPa

##### EUT Operation:

<b>Input Voltage</b> .....	:	Battery 4.5V
<b>Operating Mode</b> .....	:	On mode

### 6.3.2 Block Diagram of Setup

The Radio-frequency electromagnetic fields Immunity test was performed in accordance with the IEC 61000-4-3.



### 6.3.3 Test Results

Frequency	Face of EUT	Antenna polarisation	Test Level	Step Size	Dwell Time	Performance Criterion	Result
80 to 1000MHz	Front, Back, Left, Right	Horizontal	3V/m	1%	1s	A	Pass*
80 to 1000MHz	Front, Back, Left, Right	Vertical	3V/m	1%	1s	A	Pass*

Remark:

\* During the test no deviation was detected to the selected operation mode(s)

## 7 Photographs – Test Setup

### 7.1 Photograph – Radiated Electromagnetic Disturbance Test Setup




### 7.2 Photograph – Radiated Emission Test Setup, 30MHz to 300MHz



### 7.3 Photograph – ESD Immunity Test Setup



### 7.4 Photograph – Radio-Frequency Electromagnetic Fields Immunity Test Setup





## 8 Photographs – Constructional Details

### 8.1 EUT – External View



## 8.2 EUT – Internal View



===== End of Report =====